



REGOMS PRODUCT DATASHEET

Water Glycol Flushing Pump



WATER GLYCOL FLUSHING PUMP

SPECIFICATIONS

WEIGHT	APPROX 1,500KG
DIMENSION	1,750MM (L) X 1,300MM (W) X 1,700MM(H)
MAXIMUM WORKING PRESSURE	200 BAR (2900 PSI)
MAXIMUM FLOW RATE	106LPM
BUILT IN TANK CAPACITY	280 LITRES
CONNECTION	INLET 1 X 1" FEMALE NPT, 2 X ½" FEMALE NPT, OUTLET 1 X 1" FEMALE NPT, 2 X ½" FEMALE NPT
POWER	400 -415V/3PM/50HZ/STAR DELTA STARTER
PUMP	PRATISSOLU KF-30 TRIPLEX PLUNGER PUMP
E-MOTOR	WONDER ELECTRIC IE1-280S-6/B3/45KW
FILTRATION	PRE-FILTER – STAINLESS STEEL 40UM 600MM X 250MM RETURN FILTER ELEMENT – 3UM PALL UE219AS13H
LIFTING SET	SLING AND SHACKLE CONFORMING TO DNV 2.7-1
APPROVAL	DNV 2.7-1, ISO 10855-1

For a quotation and detailed pricing, please contact our sales team:

REGOMS Engineering (M) Sdn.

Bhd. No. 10-1, Jalan 13/48A, The
Boulevard Shop Office Sentul Raya,
Sentul Selatan, 51000 KL. WP.
Malaysia
Tel: +603 4050 6485
Email: sales1@regoms.com

REGOMS Australia Pty Ltd.

Level 1, 16, McDougall Street,
PO Box 1279, MILTON QLD
4064Australia
M: +614 0008 4977
F: +617 3198 2401
Email:sales1@regoms.com

Any modification of the content, duplication or reprinting of this datasheet, as well as any distribution to third parties - even in parts - shall require the express written approval of REGOMS.